

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SDS Ref. (EU): RC-OG

Issue date: 25/09/2017 Revision date: 20/04/2020 Supersedes: 20/08/2019 Version: 2.0

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : RAPTOR COLOUR - OLIVE GREEN

Product code : UP4865

Type of product : Colouring agents

Product group : Paint tint

Other means of identification : RAL 6003

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Intended for general public

Main use category : Industrial use, Professional use, Consumer use

Use of the substance/mixture : Colouring agents Function or use category : Colouring agents

## 1.2.2. Uses advised against

No additional information available

# 1.3. Details of the supplier of the safety data sheet

U-POL LIMITED Denington Road

NN8 2QH Wellingborough - United Kingdom

T +44 (0) 1933 230310

technicalsupport@u-pol.com - www.u-pol.com

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC - +44 (0) 870 8200418 (24 hrs)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	NHS England, Scotland & Wales	-	Call 111 or a Doctor	In Northern Ireland, contact your local GP or pharmacist during normal hours (www.gpoutofhours.hscni.net)

#### **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226

Full text of H statements : see section 16

#### Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour.

#### 2.2. Label elements

## Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)

GHS02

Signal word (CLP) : Warning

Hazard statements (CLP) : H226 - Flammable liquid and vapour.

Precautionary statements (CLP) : P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, open flames, sparks. — No smoking.

P280 - Wear eye protection, protective clothing, protective gloves.

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

EUH-statements : EUH066 - Repeated exposure may cause skin dryness or cracking.

EN (English) 1/12

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

#### 2.3. Other hazards

No additional information available

# **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-methoxy-1-methylethyl acetate substance with a Community workplace exposure limit	(CAS-No.) 108-65-6 (EC-No.) 203-603-9 (EC Index-No.) 607-195-00-7 (REACH-no) 01-2119475791-29	5 – 20	Flam. Liq. 3, H226
n-butyl acetate substance with a Community workplace exposure limit	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1 (REACH-no) 01-2119485493-29	3 – 10	Flam. Liq. 3, H226 STOT SE 3, H336
n-butyl acetate substance with a Community workplace exposure limit	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1 (REACH-no) 01-2119485493-29	1 – 2.5	Flam. Liq. 3, H226 STOT SE 3, H336

Full text of H-statements: see section 16

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

: Rinse skin with water/shower. Take off immediately all contaminated clothing. First-aid measures after skin contact

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

# 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour. Hazardous decomposition products in case of fire : Toxic fumes may be released

5.3. Advice for firefighters

: Do not attempt to take action without suitable protective equipment. Self-contained Protection during firefighting

breathing apparatus. Complete protective clothing.

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

**Emergency procedures** : Ventilate spillage area. No open flames, no sparks, and no smoking.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

# 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or

public waters.

Other information : Dispose of materials or solid residues at an authorized site.

## 6.4. Reference to other sections

For further information refer to section 13.

25/09/2017 (Version: 1.0) 2/12 EN (English)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

## **SECTION 7: Handling and storage**

7.1. Precautions for safe handling

Precautions for safe handling

: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment.

Hygiene measures

: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

# 7.3. Specific end use(s)

No additional information available

# SECTION 8: Exposure controls/personal protection

	0.1.	Control	parameters	
ı				

2-methoxy-1-methylethyl acetate (108-65-6)		
EU	Local name	2-Methoxy-1-methylethylacetate
EU	IOELV TWA (mg/m³)	275 mg/m³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m³)	550 mg/m³
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	Skin
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Ireland	Local name	2-Methoxy-1-methylethylacetate
Ireland	OEL (8 hours ref) (mg/m³)	275 mg/m³
Ireland	OEL (8 hours ref) (ppm)	50 ppm
Ireland	OEL (15 min ref) (mg/m3)	550 mg/m³
Ireland	OEL (15 min ref) (ppm)	100 ppm
Ireland	Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Ireland	Regulatory reference	Chemical Agents Code of Practice 2020
United Kingdom	Local name	1-Methoxypropyl acetate
United Kingdom	WEL TWA (mg/m³)	274 mg/m³
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m³)	548 mg/m³
United Kingdom	WEL STEL (ppm)	100 ppm
United Kingdom	Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
United Kingdom	Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

n-butyl acetate (123-86-4)		
EU	Local name	n-Butyl acetate
EU	IOELV TWA (mg/m³)	241 mg/m³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m³)	723 mg/m³
EU	IOELV STEL (ppm)	150 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831
Ireland	Local name	Butyl acetate

25/09/2017 (Version: 1.0) EN (English) 3/12

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

n-butyl acetate (123-86-4)		
Ireland	OEL (8 hours ref) (mg/m³)	710 mg/m³
Ireland	OEL (8 hours ref) (ppm)	150 ppm
Ireland	OEL (15 min ref) (mg/m3)	950 mg/m³
Ireland	OEL (15 min ref) (ppm)	200 ppm
Ireland	Regulatory reference	Chemical Agents Code of Practice 2020
United Kingdom	Local name	Butyl acetate
United Kingdom	WEL TWA (mg/m³)	724 mg/m³
United Kingdom	WEL TWA (ppm)	150 ppm
United Kingdom	WEL STEL (mg/m³)	966 mg/m³
United Kingdom	WEL STEL (ppm)	200 ppm
United Kingdom	Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

n-butyl acetate (123-86-4)		
EU	Local name	n-Butyl acetate
EU	IOELV TWA (mg/m³)	241 mg/m³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m³)	723 mg/m³
EU	IOELV STEL (ppm)	150 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831
Ireland	Local name	Butyl acetate
Ireland	OEL (8 hours ref) (mg/m³)	710 mg/m³
Ireland	OEL (8 hours ref) (ppm)	150 ppm
Ireland	OEL (15 min ref) (mg/m3)	950 mg/m³
Ireland	OEL (15 min ref) (ppm)	200 ppm
Ireland	Regulatory reference	Chemical Agents Code of Practice 2020
United Kingdom	Local name	Butyl acetate
United Kingdom	WEL TWA (mg/m³)	724 mg/m³
United Kingdom	WEL TWA (ppm)	150 ppm
United Kingdom	WEL STEL (mg/m³)	966 mg/m³
United Kingdom	WEL STEL (ppm)	200 ppm
United Kingdom	Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

# 8.2. Exposure controls

# Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:	
Protective gloves	
Eye protection:	
Safety glasses	
Skin and body protection:	
Wear suitable protective clothing	
Respiratory protection:	
In case of insufficient ventilation, wear suitable respiratory equipment	

25/09/2017 (Version: 1.0) 20/04/2020 (Version: 2.0) EN (English) 4/12

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

#### Personal protective equipment symbol(s):



#### Environmental exposure controls:

Avoid release to the environment.

## **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Physical state : Liquid Appearance : Liquid. Colour : Green. Odour : strong.

Odour threshold : No data available pН : No data available Relative evaporation rate (butylacetate=1) : No data available Melting point : Not applicable Freezing point : No data available Boiling point : No data available

: 39 °C Flash point

Auto-ignition temperature : No data available Decomposition temperature : No data available Flammability (solid, gas) : Not applicable : No data available Vapour pressure Relative vapour density at 20 °C : No data available Relative density : No data available Density : 1.68 g/cm<sup>3</sup> Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available : No data available Viscosity, kinematic · No data available Viscosity, dynamic Explosive properties : No data available Oxidising properties : No data available

9.2. Other information

VOC content : 350 g/l

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

**Explosive limits** 

Flammable liquid and vapour.

#### 10.2. Chemical stability

Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

## 10.5. Incompatible materials

No additional information available

# 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

: No data available

# **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified : Not classified Acute toxicity (dermal) Acute toxicity (inhalation) : Not classified

5/12 25/09/2017 (Version: 1.0) EN (English)

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830		
2-methoxy-1-methylethyl acetate (108-65-6)		
LD50 oral rat	6190 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
LD50 dermal rabbit	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal)	
LC50 inhalation rat (ppm)	1728 ppm/4h (4 h, OECD Guideline 403 (Acute Inhalation Toxicity), rat, male/female, Inhalation, vapours)	
n-butyl acetate (123-86-4)		
LD50 oral rat	10760 – 12789 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral)	
LD50 dermal rabbit	14112 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal)	
n-butyl acetate (123-86-4)		
LD50 oral rat	10760 – 12789 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral)	
LD50 dermal rabbit	14112 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal)	
LC50 inhalation rat (ppm)	390 ppm/4h	
LC50 inhalation rat (Vapours - mg/l/4h)	> 21 mg/l/4h (4 h, OECD Test Guideline 403, rat, vapours)	
titanium(IV) oxide (13463-67-7)		
LD50 oral rat	> 5000 mg/kg bodyweight (OECD 425: Acute Oral Toxicity: Up-and-Down Procedure, Rat, Female, Experimental value, Oral, 14 day(s))	
LC50 inhalation rat (mg/l)	> 6.82 mg/l (Other, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))	
aluminium oxide, activated (1344-28-1)		
LD50 oral rat	> 15900 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)	
tetrapropylenebenzene (25265-78-5)		
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal))	
LD50 dermal rabbit	> 10200 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
[N,N,N',N',N",N"-hexaethyl-29H,31H-ft-alocyar	ninetrimethylaminato(2-)-N29,N30,N31,N32]copper (28654-73-1)	
LD50 oral rat	> 10000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
LD50 dermal rat	> 2500 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
Copperphthalocyanine (147-14-8)		
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
LD50 dermal rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
carbon black (1333-86-4)		
LD50 oral rat	> 10000 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 28 day(s))	

25/09/2017 (Version: 1.0) 20/04/2020 (Version: 2.0) EN (English) 6/12

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

according to Regulation (EC) No. 1907/2006 (REACH) with its	s amendment Regulation (EU) 2015/830
LC50 inhalation rat (mg/l)	> 4.6 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Experimental value, Inhalation (dust))
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
aluminium oxide, activated (1344-28-1)	
NOAEL (animal/male, F0/P)	1000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
3101-repeated exposure	. Not classified
2-methoxy-1-methylethyl acetate (108-65-6)	
NOAEL (oral, rat, 90 days)	≥ 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
aluminium oxide, activated (1344-28-1)	
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.07 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
tetrapropylenebenzene (25265-78-5)	
NOAEL (oral, rat, 90 days)	200 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents), Guideline: EU Method B.7 (Repeated Dose (28 Days) Toxicity (Oral))
[N,N,N',N',N",N"-hexaethyl-29H,31H-ft-alocya	ninetrimethylaminato(2-)-N29,N30,N31,N32]copper (28654-73-1)
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Copperphthalocyanine (147-14-8)	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: other:Guideline for 28-Day Repeated Dose Toxicity Test in Mammalian Species (Chemical Substances Control Law of Japan)
Aspiration hazard	: Not classified
SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified
2-methoxy-1-methylethyl acetate (108-65-6)	
LC50 fish 1	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 Daphnia 1	> 500 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 72h algae (1)	> 1000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
-	·

25/09/2017 (Version: 1.0) 20/04/2020 (Version: 2.0) EN (English)

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EC50 96h algae (1)	> 1000 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'

n-butyl acetate (123-86-4)	
LC50 fish 1	18 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
EC50 Daphnia 1	44 mg/l (48 h, Daphnia sp., Static system, Fresh water, Experimental value)
EC50 72h algae (1)	674.7 mg/l (Desmodesmus subspicatus, Static system, Fresh water, Experimental value)
NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

n-butyl acetate (123-86-4)			
LC50 fish 1	18 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)		
LC50 fish 2	62 mg/l (Leuciscus idus, static system)		
EC50 Daphnia 1	44 mg/l (48 h, Daphnia sp., Static system, Fresh water, Experimental value)		
EC50 72h algae (1)	674.7 mg/l (Desmodesmus subspicatus, Static system, Fresh water, Experimental value)		
NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
NOEC chronic crustacea	23 mg/l		

# 12.2. Persistence and degradability

# 2-methoxy-1-methylethyl acetate (108-65-6)

Persistence and degradability Readily biodegradable in the soil. Readily biodegradable in water.

n-butyl acetate (123-86-4)			
Persistence and degradability Readily biodegradable in water.			
ThOD	2.21 g O <sub>2</sub> /g substance		
BOD (% of ThOD) 0.46			

n-butyl acetate (123-86-4)		
Persistence and degradability Readily biodegradable in water.		
ThOD	2.21 g O <sub>2</sub> /g substance	
BOD (% of ThOD)	0.46	

# 12.3. Bioaccumulative potential

	2-methoxy-1-methylethyl acetate (108-65-6)		
Partition coefficient n-octanol/water (Log Pow)  1.2 (Experimental value, Equivalent or similar to OECD 117, 20 °C)			
Bioaccumulative potential		Low potential for bioaccumulation (Log Kow < 4).	

n-butyl acetate (123-86-4)			
BCF fish 1 15.3 (Calculated value)			
Partition coefficient n-octanol/water (Log Pow)	2.3 (Test data, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)		
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).		

n-butyl acetate (123-86-4)		
BCF fish 1	15.3 (Calculated value)	
Partition coefficient n-octanol/water (Log Pow)	2.3 (Test data, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	

25/09/2017 (Version: 1.0) EN (English) 8/12

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.4. Mobility in soil				
2-methoxy-1-methylethyl acetate (108-65-6)				
Surface tension	29.4 mN/m (20 °C, 100 vol %, EU Method A.5: Surface tension)			
Partition coefficient n-octanol/water (Log Koc)	0.264 (log Koc, QSAR)			
Ecology - soil	Highly mobile in soil.			

n-butyl acetate (123-86-4)			
Surface tension 0.0163 N/m (20 °C)			
Partition coefficient n-octanol/water (Log Koc) 1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, QSAR)			
Ecology - soil Low potential for adsorption in soil.			

n-butyl acetate (123-86-4)			
Surface tension 0.0163 N/m (20 °C)			
Partition coefficient n-octanol/water (Log Koc) 1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, QSAR)			
Ecology - soil	Low potential for adsorption in soil.		

# 12.5. Results of PBT and vPvB assessment

Component			
2-methoxy-1-methylethyl acetate (108-65-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII		
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII		
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII		

# 12.6. Other adverse effects

No additional information available

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Flammable vapours may accumulate in the container.

# **SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

In accordance with ADR / RID / IMDG / IATA / ADN							
ADR	IMDG	IATA	ADN	RID			
14.1. UN number	14.1. UN number						
1263	1263	1263	1263	1263			
14.2. UN proper shippin	g name			•			
PAINT	PAINT	Paint	PAINT	PAINT			
Transport document descr	iption						
UN 1263 PAINT, 3, III, (D/E)	UN 1263 PAINT, 3, III						
14.3. Transport hazard	class(es)						
3	3	3	3	3			
3	3	3	3	3			
14.4. Packing group							
III	III	III	III	III			

25/09/2017 (Version: 1.0) EN (English) 9/12 20/04/2020 (Version: 2.0)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

# 14.6. Special precautions for user

# **Overland transport**

Classification code (ADR) : F1

Special provisions (ADR) : 163, 367, 650

Limited quantities (ADR) : 51 Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

: PP1 Special packing provisions (ADR) : MP19 Mixed packing provisions (ADR) Portable tank and bulk container instructions : T2

(ADR)

Portable tank and bulk container special provisions

(ADR)

: TP1, TP29

Tank code (ADR) : LGBF Vehicle for tank carriage : FL : 3 Transport category (ADR) Special provisions for carriage - Packages (ADR) : V12 Special provisions for carriage - Operation (ADR) : S2 Hazard identification number (Kemler No.) : 30

Orange plates

**30** 1263

Tunnel restriction code (ADR) : D/E EAC code : •3YE

## Transport by sea

Special provisions (IMDG) : 163, 223, 955, 367

Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) Packing instructions (IMDG) : P001, LP01 : PP1 Special packing provisions (IMDG) IBC packing instructions (IMDG) : IBC03 Tank instructions (IMDG) : T2 Tank special provisions (IMDG) : TP1, TP29 EmS-No. (Fire) : F-E EmS-No. (Spillage) : S-F Stowage category (IMDG) : A

Properties and observations (IMDG) : Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA) : E1 PCA Limited quantities (IATA) : Y344 PCA limited quantity max net quantity (IATA) : 10L PCA packing instructions (IATA) : 355 PCA max net quantity (IATA) : 60L CAO packing instructions (IATA) : 366 CAO max net quantity (IATA) : 220L

Special provisions (IATA) : A3, A72, A192

: 3L ERG code (IATA)

Inland waterway transport

: F1 Classification code (ADN)

Special provisions (ADN) : 163, 367, 650

Limited quantities (ADN) : 5 L

25/09/2017 (Version: 1.0) 10/12 EN (English)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Excepted quantities (ADN) : E1

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01

Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : F1

Special provisions (RID) : 163, 367, 650

Limited quantities (RID) : 5L Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

 Special packing provisions (RID)
 : PP1

 Mixed packing provisions (RID)
 : MP19

 Portable tank and bulk container instructions (RID)
 : T2

Portable tank and bulk container special provisions : TP1, TP29

(RID)

Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12
Colis express (express parcels) (RID) : CE4
Hazard identification number (RID) : 30

# 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:		
3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	RAPTOR COLOUR - OLIVE GREEN ; 2-methoxy-1-methylethyl acetate ; n-butyl acetate ; QBA - n-butyl acetate	
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	n-butyl acetate ; QBA - n-butyl acetate	
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	RAPTOR COLOUR - OLIVE GREEN ; 2-methoxy-1-methylethyl acetate ; n-butyl acetate ; QBA - n-butyl acetate	

Contains no substance on the REACH candidate list Contains no REACH Annex XIV substances

VOC content : 350 g/l

Directive 2012/18/EU (SEVESO III)

# 15.1.2. National regulations

No additional information available

# 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

# **SECTION 16: Other information**

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate

25/09/2017 (Version: 1.0) EN (English) 11/12 20/04/2020 (Version: 2.0)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Full text of H- and EUH-statements:	
Flam. Liq. 3	Flammable liquids, Category 3
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### SDS EU (REACH Annex II)

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.